

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 15/07/2016 Revision date: 23/10/2017 Supersedes: 14/04/2015 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : 6967 - BLOCJELT ROUGE

Product code : 006967

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial

For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ITW Spraytec 42, rue Galliéni

F-92600 Asnières sur Seine - France

T +33(0)1.40.80.32.32 - F +33(0)1.40.80.32.30

infofds@itwpc.com - www.jelt.fr

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 Serious eye damage/eye irritation, Category H319

2

Specific target organ toxicity — Single H336

exposure, Category 3, Narcosis

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Hazardous ingredients : n-butyl acetate; ethyl acetate; propan-2-ol, isopropyl alcohol, isopropanol

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 - Use only outdoors or in a well-ventilated area.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to Collection point

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

22/12/2017 EN (English) 1/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	20 - 40	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	20 - 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Nitrocellulose	(CAS-No.) 9004-70-0 (EC-No.) 239-069-9	< 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319
propan-2-ol, isopropyl alcohol, isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2,4-dihydroxybenzophenone	(CAS-No.) 131-56-6 (EC-No.) 205-029-4	< 1	Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a POISON CENTER/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water haze. Carbon dioxide. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of : Thermal decomposition generates : fume. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

22/12/2017 EN (English) 2/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Avoid release to the environment.

Methods and material for containment and cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public Methods for cleaning up

: Dispose of materials or solid residues at an authorized site. Other information

Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product. Always wash hands after handling the Hygiene measures

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Storage conditions

Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters n butul costate (122 96 4)

n-butyl acetate (123-86-4)		
France	Local name	Acétate de n-butyle
France	VME (mg/m³)	710 mg/m³
France	VME (ppm)	150 ppm
France	VLE (mg/m³)	940 mg/m³
France	VLE (ppm)	200 ppm
Germany	Local name	n-Butylacetat
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	300 mg/m³
Germany	TRGS 900 Occupational exposure limit value (ppm)	62 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m³)	600 mg/m³
Germany	TRGS 900 Limitation of exposure peaks (ppm)	124 ppm
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m³)	724 mg/m³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	966 mg/m³
United Kingdom	WEL STEL (ppm)	200 ppm
ethyl acetate (141-78-6)		
France	Local name	Acétate d'éthyle
France	VME (mg/m³)	1400 mg/m³
France	VME (ppm)	400 ppm
Germany	Local name	Ethylacetat
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	1500 mg/m³
Germany	TRGS 900 Occupational exposure limit value (ppm)	400 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m³)	3000 mg/m³
Germany	TRGS 900 Limitation of exposure peaks (ppm)	800 ppm
United Kingdom	Local name	Ethyl acetate
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (ppm)	400 ppm

22/12/2017 EN (English) 3/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
France	Local name	propane-2-ol, alcool isopropylique, isopropanol
France	VLE (mg/m³)	980 mg/m³
France	VLE (ppm)	400 ppm
Germany	Local name	2-Propanol, Isopropylalkohol, Isopropanol
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	500 mg/m³
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m³)	1000 mg/m³
Germany	TRGS 900 Limitation of exposure peaks (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

In case of repeated or prolonged contact wear gloves. The choice of appropriate gloves depends not only on the material, but also on other quality criteria that may vary from one manufacturer to another. As the product is a preparation made from several substances, glove material resistance may not be calculated in advance and must be tested before use. The exact penetration time of glove material is to be determined by the manufacturer of protective gloves and respected.

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : red.

Odour
Odour : Organic solvent.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : > 77 °C Flash point : < 21 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available

Density : 1 g/cm³

Solubility : insoluble in water, soluble in most organic solvents.

Log Pow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

22/12/2017 EN (English) 4/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Heating may cause a fire or explosion. Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates: fume. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	23.4 mg/l/4h

ethyl acetate	(141-78-6)
---------------	------------

5		
	LD50 oral rat	> 2000 mg/kg
	LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

n-butyl acetate (123-86-4)		
LC50 fish 1	18 mg/l	
EC50 Daphnia 1	44 mg/l	
ErC50 (algae)	647,7 mg/l	
NOEC chronic algae	200 mg/l	
ethyl acetate (141-78-6)		

LC50 fish 1	> 100 mg/l
EC50 other aquatic organisms 1	> 100 mg/l

22/12/2017 EN (English) 5/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl acetate (141-78-6)	
ErC50 (algae)	> 100 mg/l

12.2. Persistence and degradability

ethyl acetate (141-78-6)	
Biodegradation	> 70 % OCDE 301 D 28 days

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
Log Kow	2,3
ethyl acetate (141-78-6)	
Log Pow	0,68

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with IATA / ADR / IMDG

ADR	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. UN proper shipping name		
PAINT	PAINT	Paint related material
Transport document description		
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II	UN 1263 Paint related material, 3, II
14.3. Transport hazard class(es)		
3	3	3
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 163, 640D, 650, 367

Limited quantities (ADR) : 5l Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions : T4

(ADR)

Portable tank and bulk container special : TP1, TP8, TP28

provisions (ADR)

22/12/2017 EN (English) 6/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation : S2, S20

(ADR)

Hazard identification number (Kemler No.) : 33

Orange plates :

33 1263

Tunnel restriction code (ADR) : D/E

- Transport by sea

Special provisions (IMDG) : 163
Limited quantities (IMDG) : 500 ml
Excepted quantities (IMDG) : E3
Packing instructions (IMDG) : P001
Tank instructions (IMDG) : T11

Tank special provisions (IMDG) : TP1, TP8, TP27

EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : E

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to waters (Classification according to AwSV,

Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen - Borstvoeding

22/12/2017 EN (English) 7/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

/ruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

: None of the components are listed

: None of the components are listed

Denmark

Class for fire hazard : Class I-1 Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids

must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the

product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Tall tox of IT and Earl statements.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

22/12/2017 EN (English) 8/8