

ENG

Translation of the
original user guide



LAWN MOWER RASION 2 SMART

Operating instructions

59_143879-B
09/2020

READ THE USER GUIDE CAREFULLY BEFORE USE

   #LOVEELECTRIC

PELLENC

TABLE OF CONTENTS

1. INTRODUCTION	5
2. SAFETY	6
2.1. GENERAL SAFETY WARNINGS	6
2.1.1. TRAINING	6
2.1.2. PREPARATION	6
2.1.3. OPERATION	6
2.1.4. MAINTENANCE AND STORAGE	7
2.2. SAFETY MEASURES ASSOCIATED WITH CHARGER AND BATTERY USE	7
2.3. PERSONAL PROTECTION EQUIPMENT	7
2.4. SAFETY SIGNAGE	8
3. DESCRIPTION AND FEATURES	9
3.1. TECHNICAL CHARACTERISTICS	9
3.2. NOISE LEVELS	10
4. COMMISSIONING	11
4.1. UNFOLD THE MOWER INTO THE WORKING POSITION	11
4.2. COLLECTING BIN CAPACITY	13
4.3. INSTALLATION OF A BATTERY TRAY	13
4.4. 750 / 1200 / 1500 BATTERY: INSTALLATION AND CONNECTION	14
4.5. ALPHA 260 / 520 BATTERY: INSTALLATION AND CONNECTION	15
5. USE	17
5.1. TURN THE BATTERY ON / OFF	17
5.2. SETTINGS	17
5.2.1. CONTROL UNIT	18
5.2.2. ADJUSTING THE TRAVEL SPEED	18
5.2.3. ADJUSTING THE ROTATIONAL SPEED OF THE BLADES	18
5.2.4. ADJUSTING THE CUTTING HEIGHT	20
5.3. CONTROLS	21
5.3.1. STEERING CONTROLS	21
5.3.2. BOOST OF MOVEMENT FUNCTION	21
5.3.3. MOWING CONTROLS	22
5.3.4. THE BOOST FUNCTION	22
5.3.5. COMBINATION OF CONTROLS	23
5.3.6. LOCK / UNLOCK THE FRONT WHEELS DIRECTION	24
5.3.7. ENABLE/DISABLE THE PARKING BRAKE/TRANSPORT BRAKE	24
5.4. IMMOBILIZER SYSTEM	25
5.4.1. SECURITY KEY	25
5.4.2. INCLINOMETER	26
5.5. ADVICE FOR USE	26
5.5.1. MOWING METHOD	27
5.5.2. CUTTING HEIGHT	27

5.5.3. SLOPES 28
 5.5.4. DAMP GROUND 28
 5.5.5. MOWING WITH GRASS COLLECTION 28
 5.5.6. MOWING WITHOUT GRASS COLLECTION 29
 5.5.7. MOWING WASTE 29

6. MAINTENANCE 30

6.1. MAINTENANCE FREQUENCY 30
 6.2. USEFUL ADVICE FOR RISK FREE MAINTENANCE 31
 6.2.1. CUTTING BLADES 31
 6.2.2. CUTTER HOUSING 32
 6.2.3. WHEELS 33
 6.2.4. COLLECTING BIN 33
 6.2.5. CLEANING THE OPTICAL SENSOR 33

7. INCIDENTS AND TROUBLESHOOTING 34

8. STORAGE AND TRANSPORT 36

8.1. FOLD THE MOWER INTO THE TRANSPORT POSITION 36
 8.2. STORAGE 37
 8.3. OFF-SEASON STORAGE 38

9. ACCESSORIES AND CONSUMABLES 38

10. GENERAL WARRANTIES 39

10.1. STATUTORY WARRANTY 39
 10.1.1. LATENT DEFECTS WARRANTY 39
 10.1.2. LEGAL WARRANTY OF CONFORMITY 39
 10.2. COMMERCIAL WARRANTY PELLENC 40
 10.2.1. CONTENT 40
 10.2.2. DURATION OF THE WARRANTY 40
 10.2.3. IMPLEMENTATION OF THE COMMERCIAL WARRANTY 41
 10.3. PAID AFTER-SALES SERVICE 41
 10.3.1. GENERAL INFORMATION 41
 10.3.2. WEAR PARTS AND CONSUMABLES 41
 10.3.3. SPARE PARTS 41

11. COMPLIANCE STATEMENTS 42

11.1. "EC" DECLARATION OF CONFORMITY: RASION 2 42

1. INTRODUCTION

Dear Customer,

Thank you for purchasing your Lawn mower Rasion 2 Smart . Correctly used and maintained, this tool will give a satisfactory performance for many years.



Warning

Your device contains numerous recoverable or recyclable materials. Return it to your dealer or, failing this, to an approved servicing centre to be treated.



Comply with the regulations in force in your country as concerns environmental protection associated with your activity.



Warning

It is imperative that you read through the ENTIRE user's manual before using or servicing the tool. Always comply with the instructions and illustrations in the manual.

All through this user guide you will find advisory notes and information entitled: NOTE, IMPORTANT, ATTENTION and WARNING.

The points marked "NOTE" indicate additional information.

The points marked "IMPORTANT" warn the user of a potential risk to the equipment.

The points marked "ATTENTION" warn the user of a potentially hazardous situation which if not avoided leads to minor injuries.

The points marked "WARNING" warn the user of a potentially hazardous situation which if not avoided leads to serious injury or death.

The warning  indicates that damage resulting from failure to comply with the procedures and instructions is not covered by the warranty and the owner will be liable for any repair costs.

Safety indications are also given on the tool; they remind you of the safety precautions to be taken. Identify and read these indications before using the tool. Immediately replace any indications that may become partially illegible or deteriorated.

Refer to Section 2.4, "Safety signage" for the location diagram of the safety stickers affixed to the tool.

No part of this manual may be reproduced without the written permission of the company PELLENC. The illustrations given in this manual are for information purposes and are in no way contractual. The PELLENC company reserves the right to make any modification or improvement to its products as deemed necessary without informing customers already in possession of a similar model. This manual forms an integral part of the tool and must accompany the tool if it changes hands.

2. SAFETY

2.1. GENERAL SAFETY WARNINGS



Warning

Read all safety warnings, instructions, illustrations and specifications provided with this power tool. Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury.

Note

Retain all the safety measures and instructions for later reading.

This device is not intended for use by individuals (including children) with reduced physical, sensory or mental capabilities, nor by anyone lacking in experience or knowledge, except if they are supervised or have received prior instructions from a person responsible for their safety.

- Your Lawn mower Rasion 2 Smart is a professional tool whose use is reserved exclusively for cleaning of green spaces (grass, dense grasses, woody weeds and brambles).
- The PELENC SAS company accepts no responsibility for any damage caused by improper or unspecified use different from its original intention.
- The PELENC SAS company accepts no responsibility for any damage caused by the use of non-original parts or accessories.

Operating rules to be respected for your safety when using lawn mowers with electric motors.

2.1.1. TRAINING

1. Read the instructions carefully. Become familiar with the controls and the proper use of equipment.
2. Never allow children or individuals who are unfamiliar with these instructions to use the machine. National regulations may restrict operator age.
3. Never operate the machine while other people, especially children, or pets, are nearby.
4. Keep in mind that the operator or user is responsible for any accidents caused by them and the dangers that other people or their property may run.

2.1.2. PREPARATION

1. During operation of the machine, always wear protective footwear and long trousers. Do not operate the machine barefoot or in sandals. Avoid wearing loose clothing or items with loose cords, or a tie.
2. Inspect the entire area where the machine will be used and remove all objects that might be thrown by it.
3. Before use, always visually inspect the machine to ensure that its cutting elements, bolts and the assembly in general, are not worn or damaged. Replace sets of worn or damaged components in order to maintain proper balance. Replace damaged or difficult to read labels.
4. Before use, check the power cable to detect signs of damage or aging. Immediately disconnect the battery if the cable becomes damaged during use. **Do not touch the cable before turning off the battery.** Do not use the machine if the cable is damaged or worn.

2.1.3. OPERATION

1. Only operate the machine in daylight or in good artificial light. Use safety equipment. Always wear eye protection.

2. Avoid operating the machine on wet grass. Remove any adjusting wrenches before switching the tool on.
3. Always place your feet firmly when on slopes.
4. Walk, never run.
5. Mow transversely on slopes, never up and down.
6. Be very careful when changing direction on slopes.
7. Do not mow excessively steep slopes.
8. Use the machine with extreme caution when using it in reverse or pulling it toward you.
9. Turn off the cutting elements if the machine has to be tilted for transport through non-grassy areas and when it has to be transported to or brought back from the location where it is to be used.
10. Never use the machine with defective guards or without safety devices in place, for example deflectors and/or grass catchers.
11. Start the engine, drive carefully according to instructions and with your feet at a safe distance from the cutting elements.
12. Do not put hands or feet near or under rotating parts. Never allow the ejection opening to get clogged.
13. Do not transport the machine while the power source is attached.
14. To stop the machine, turn off the battery and remove the battery connector. Make sure all moving parts have completely stopped.
15. Stop the machine and remove the power-off device. Make sure all moving parts have completely stopped
 - before leaving the machine,
 - before cleaning any jams, or emptying the chute,
 - before checking, cleaning or repairing the machine,
 - after hitting an object inspect the machine to detect any damage and carry out repairs before restarting and using it.

If the machine begins to vibrate abnormally, it is essential at once to:

- inspect the machine to see if it is damaged,
- check if any parts have worked loose, and tighten them if necessary,
- repair or replace any damaged parts.

2.1.4. MAINTENANCE AND STORAGE

1. Make sure all nuts, bolts and screws are kept tight to be sure that the equipment is in good operating condition.
2. Check for wear or damage to the grass catcher frequently.
3. Replace worn or damaged parts so that the machine remains safe.
4. Take all precautions necessary when it comes to multi-blade machines, since the rotation of one cutting element can cause all the others to rotate.
5. When adjusting the machine, avoid getting fingers caught between the moving blades and the fixed parts.
6. Always allow the machine to cool down before storing.
7. Pay attention during routine maintenance of the cutting elements, as they may still be moving, even if the power source is cut off.
8. Replace worn or damaged parts so that the machine remains safe. Only use certified spare parts and accessories.

2.2. SAFETY MEASURES ASSOCIATED WITH CHARGER AND BATTERY USE

Important

Please refer to the tool battery instructions.PELLENC

2.3. PERSONAL PROTECTION EQUIPMENT


	Equipment	Wear
1	Safety helmet	--
2	Protective visor	--

<p>00_20_028</p>	3	Protective gloves	Recommended	
	4	Safety footwear	Mandatory	
	5	Ear protection	Recommended	
	6	Protective goggles	Mandatory	
	7	Jacket or over-sleeves	Recommended	
	8	Work trousers	Recommended	

2.4. SAFETY SIGNAGE


Use the lawn mower with caution.

Pictograms on the ejection flap of the machine indicate the main precautions to be respected to avoid injury:



1. **Read the user manual**
Read the instructions carefully and follow the safety precautions.
2. **Risk of injury**
Ensure the people in the vicinity are not at risk from matter ejected from the machine.
Keep a safe distance of at least 15 meters between the machine and people in the vicinity.
3. **Caution - the cutting blades are very sharp!**
Keep your feet and hands away from the blade and the cutting area.
Remove the safety locking device before performing maintenance work and before leaving the mower unattended, regardless of the duration.
4. **Noise levels**
Sound power dB

3. DESCRIPTION AND FEATURES



- | | |
|--------------------------------------|---------------------------------|
| 1. Handle | 22. '-' button |
| 2. Control unit | 23. Lawn mower direction button |
| 3. Handle adjusting lever | 24. '+' button |
| 4. Handlebar | 25. Right reverse button |
| 5. Handlebar adjusting lever | 26. Right trigger |
| 6. Ejection flap | 27. LCD display |
| 7. 9-pin power cord | 28. Menu button |
| 8. Cutter deck housing cover | 29. Left reverse button |
| 9. 750/1200/1500 battery holder | 30. Left trigger |
| 10. Cutting height adjustment handle | 31. Security key |
| 11. Density sensor | |
| 12. Front wheels lock bolts | |
| 13. Cutter deck housing | |
| 14. Collecting bin | |
| 15. Collection bin handle | |

59_20_172

3.1. TECHNICAL CHARACTERISTICS

Model	Rasion 2 Smart
Dimensions when folded (l x w x h)	887 x 620 x 613 mm
Dimensions when unfolded (l x w x h)	1650 x 620 x 884 mm
Unladen weight (without battery or collecting bin)	30 kg
Cutting width	60 cm
Cutting height	25/35/45/55/65/75 mm
Collecting bin capacity	70 L
Weight of the empty collecting bin	2.7 kg
Cutter deck housing	Cast aluminum
Maximum power	1600 Watts
Forward speed	2/3/4 or 5 km/h
Reverse speed	2 km/h
Safety equipment	Removable security key
Sealing	IP54
Battery-life	According to use and battery type

Determination of the sound levels and vibration rates is based on the operating conditions at the nominal maximum speed.

Maximum weighted sound pressure level A (ref. 20 µPa) at the user's position	LpA = 83.5 dB(A)	K = 2.5 dB
--	------------------	------------

Values determined according to the sound measurement standards EN60335-2-77.

Symbol	Value	Unit	Reference	Remark
LWAm	92	dB(A)	1 pW	Measured sound power level
LWAg	93	dB(A)	1 pW	Guaranteed sound power level


The recording of the measured sound power level and of the guaranteed sound power level has been performed according to a procedure in accordance with directive 2000/14/EC.

Vibration emission value as per EN60335-2-77	ahW = 0.7m/s ² and K = 0.3m/s ²
--	---

3.2. NOISE LEVELS

The noise generated by the mower and the battery life both depend directly on the turning speed of the cutting blades:


The faster the blades are turning, the greater the noise and the lower the battery life. When the AUTO mode is enabled, the noise generated will increase as the rotational speed of the blades increases.



4. COMMISSIONING

In the packing box, the mower is in the transport position. The handlebar (4) is folded forwards and locked in place by the adjusting lever (5).

To start using the mower, the mower must be unfolded and in the working position.




4.1. UNFOLD THE MOWER INTO THE WORKING POSITION


Note

To be able to maneuver your lawn mower easily, chose a comfortable and agreeable working position to suit your body shape.

Unlock the handlebar adjustment lever (5) by pulling it back.




Fully tilt the handlebar (4) backwards.




Adjust the tightness using the thumb wheel.
Push back the handlebar adjustment lever (5).



Unlock the handle adjustment lever (3).




Adjust the angle of the handle (1).



Adjust the tightening by completely tilting the handle adjustment lever (3) and screwing or unscrewing its central screw.

Lock the handle adjustment lever (3) to lock the handle.




4.2. COLLECTING BIN CAPACITY

Note

The mower works like a vacuum cleaner that throws the cut grass into the collecting bin. Ensure that you always empty the collecting bin before it is full to avoid impairing the performance.

Overloading the bag may damage it. Before attaching the collecting bin to the lawn mower, always check it for holes, tears or damage.

Lift the ejection flap (6) and slide the collecting bin (14) into the notches located at the rear of the mower.



Note

Always check that the collecting bin is correctly attached to the lawn mower before you begin mowing.

4.3. INSTALLATION OF A BATTERY TRAY

The mower is equipped with the 750/1200/1500 battery support as standard. To use an Alpha 260/520 type battery, the factory-installed support must be removed and replaced by a optional suitable support.

Remove the 4 fixing screws of the pre-fitted battery tray.

Note


The Alpha 260/520 battery holder is sold with the harness.

Remove the battery holder from the harness before installing it on the mower.

Remove the battery tray that is to be replaced.

Place the alternative battery tray on the frame tube.

Install and tighten the 4 fixing screws of the battery tray.




4.4. 750 / 1200 / 1500 BATTERY: INSTALLATION AND CONNECTION

Check the battery life before use. If necessary, recharge the battery using the charger supplied with the battery (See the battery instruction manual).


Slide the battery from the rear into the upper hook of the battery tray (9).

Clip the front of the battery into the lower hook of the battery tray (9).

Check that the battery is completely locked on the tray.




To remove the battery from the battery tray (9), lift it while pressing the release button.



Before electrically connecting the battery to the mower, check that the battery power indicator is off.


The power indicator (represented by a flash) should not be visible on the battery display.



59N_18_041

Connect the power cable (7) of the mower to the battery connector

Screw up tight and check that the cable is properly connected.



59N_18_042



Caution


To prolong the life of the connectors, it is advisable to protect them when they are disconnected. Therefore, avoid leaving the connector in contact with abrasive or dirty surfaces, or subjecting it to major impacts (falls).

4.5. ALPHA 260 / 520 BATTERY: INSTALLATION AND CONNECTION

After having installed the appropriate battery tray, the procedure for installing an Alpha 260 / 520 type battery is identical.

Check the battery life before use. If necessary, recharge the battery using the charger supplied with the battery.


Slide the battery onto the guide of the battery tray.



59N_19_033


Move the battery along the guide until the locking clip holds the battery in place.

Check that the battery is completely locked on the tray with the battery safety lock.



Then connect the end of the mower cable to the battery (23) taking care to align the polarizers.

Screw up tight and check that the cable is properly connected.



Caution

To prolong the life of the connectors, it is advisable to protect them when they are disconnected. Therefore, avoid leaving the connector in contact with abrasive or dirty surfaces, or subjecting it to major impacts (falls).

5. USE


The mower is now ready for use but before starting to mow, the battery must be turned on. Proceed as indicated below:

5.1. TURN THE BATTERY ON / OFF


750 / 1200 / 1500 battery: Turn on the battery by pressing the upper or lower push button (battery power icon present).

Note

When the battery is connected to the mower, the battery display is turned towards the handlebar, so that it is visible from the operator's position.



Alpha 260 / 520 battery: Turn on the battery by pressing the push button on the Alpha 260 / 520 battery support.



5.2. SETTINGS

Wait for the display to stabilize at the last set speed value A-2, A-3, A-4 or A-5 before making adjustments.

5.2.1. CONTROL UNIT


The following settings are adjusted from the control unit (2):

- the forward speed of the lawn mower (A)
- the turning speed of the cutting blades (C)
- the cutting height (H)

To switch from one setting to another, press the 'menu' button (28)

To increase the value of a setting, press on '+' (24)

To decrease the value of a setting, press on '-' (22)




5.2.2. ADJUSTING THE TRAVEL SPEED

This is a self-propelled mower. When the forward switch is activated, the engines drive the rear wheels and the mower moves forward on its own, leaving you to guide it. The self-propelling motor provides significant help for effortless mowing of garden slopes or embankments.

If necessary, press on the 'menu' button (20) until you reach the forward speed setting adjuster (represented by the letter A):

As required, press on the '+' (24) or '-' (22) button to select one of the four possible settings:

- A-2: with traction, slowest speed (2 km/h)
- A-3: with traction, moderate speed (3 km/h)
- A-4: with traction, accelerated speed (4 km/h)
- A-5: with traction, top speed (5 km/h)




5.2.3. ADJUSTING THE ROTATIONAL SPEED OF THE BLADES


Two different setting modes are possible:

- 5.2.3.1. AUTOMATIC BLADE SPEED:

The density sensor (11) at the front of the lawn mower can be used to automatically adjust the turning speed of the cutting blades that varies between 3000 and 5000 rpm depending on the density of the grass. For the mower adapt the turning speed of the cutting blades automatically, set the lawn mower in C-H mode.



When the optical sensor is covered with dirt, it can no longer analyse the density and the height of the grass to be cut. The lawn mower therefore stops the blades from turning and the displays the message 'OPT'. To clean the density sensor (11), see Section 6.2.5, "Cleaning the optical sensor"



If you wish to continue working regardless, switch to manual mode and choose one of the four turning speeds C-1, C-2, C-3 or C-4 and clean the sensor later.

- 5.2.3.2. MANUAL BLADE SPEED:


You can also manage the turning speed of the cutting blades manually by configuring the lawn mower in one of the three possible settings C-1, C-2, C-3 or C-4.

The thicker and higher the grass, the faster the turning speed of the blades should be.

- 5.2.3.3. SELECTING THE TYPE OF TURNING SPEED:

Press the 'menu' button (28) until you reach the menu corresponding to the adjustment of the rotational speed of the cutting blades represented by the letter C. Then press on the '+' (24) or '-' (22) button to select the blades rotational speed type:

- C-H: auto-adjusted speed: 3000 to 5000 rpm
- C-1: manual speed 1: 3,000 rpm
- C-2: manual speed 2: 3,666 rpm
- C-3: manual speed 3: 4,333 rpm
- C-4: manual speed 4: 5,000 rpm



Note

The blades continue to rotate as long as the right trigger (26), used to make the mower move forwards, remains pressed. This means that you can release the left trigger (30) whilst mowing. When the right trigger (26) is released, the blades stop rotating at the same time as the mower stops moving.


You can use the mower's motor to move it without turning the cutting blades.

5.2.4. ADJUSTING THE CUTTING HEIGHT

The distance between the cutting blades and the ground can be configured electronically in order to adapt the cutting height to your needs. There are 6 different settings available at 10 mm intervals from 25 mm at the shortest to 75 mm at the highest.

Press on the 'menu' button (28) until you reach the cutting height setting (represented by the letter H). If necessary, press on the '+' (24) or '-' (22) button to select the setting of your choice:

- H0: Parking brake/transport brake
- H25: 25 mm between the ground and the cutting blades
- H35: 35 mm between the ground and the cutting blades
- H45: 45 mm between the ground and the cutting blades
- H55: 55 mm between the ground and the cutting blades
- H65: 65 mm between the ground and the cutting blades
- H75: 75 mm between the ground and the cutting blades



Note

If the grass you are mowing is thick, you may need to go over it several times to obtain a uniform cut.

Note

If in doubt about which cutting height to choose, always start mowing with the highest cutting height. Examine the result on a small area and, if necessary, adjust the cutting height again, being careful not to cut more than 1/3 of the height of the grass.

5.3. CONTROLS


5.3.1. STEERING CONTROLS

Control 1: Forward movement

- Press on the right trigger (26) and hold it down to move the lawn mower forwards.

Control 2: Reverse movement

- Press on the 'right reverse' button (25) and hold it down to move the lawn mower backwards. Reverse speed: 2 km/h

**Note**

-The speed at which the lawn mower moves is progressive, i.e. the more the right trigger (26) is pressed down, the more the speed increases until you reach the set speed.


As the blades do not need to be turning in order to move forwards, backwards or turn, you can use this control to move the lawn mower.

Control 3: Turning right

- Press the 'lawn mower direction' button (23) to the left to stop the rear right wheel from moving forwards. This will make the lawn mower turn on the spot to the right.

Control 4: Turning left

- Press the 'lawn mower direction' button (23) to the right to stop the rear left wheel from moving forwards. This will make the lawn mower turn on the spot to the left.

**Note**


This control can be used at the same time as you move forwards (right trigger (26) held down) or reverse (reverse button (25) pressed down) to change direction for example or when you reach the end of the mowing area.

The mower can also be turned manually using the free wheels at the front, without using the 'lawn mower direction' button (23).

5.3.2. BOOST OF MOVEMENT FUNCTION

The boost function lets the mower accelerate to its max speed of 5 km/hr.


Only when the blades and wheels are stationary, press twice quickly on the right trigger (26) and hold it after the second press to activate the Boost function. The mower then accelerates to its max speed of 5 km/hr, as long as the forward trigger is held pressed. If it is released, the mower stops moving forward.



5.3.3. MOWING CONTROLS

Control 5: Rotation of the cutting blades

- Press the 'left reverse' button (29) and release it
- Press on the left trigger (30) and hold it




Note

- The rotation speed of the cutting blades can be set in the 'C' menu.
- The speed of the cutting blades varies automatically according to the difficulty of the terrain in C-H mode
- The speed of the cutting blades can be set manually: C-1 = 3000 rpm; C-2 = 3666 rpm; C-3 = 4333 rpm; C-4 = 5000 rpm.
- The cutting blades continue to turn as long as a trigger (right or left) is pressed. When the 2 triggers are released, the cutting blades stop turning.

5.3.4. THE BOOST FUNCTION

The Boost function allows the cutting blades to accelerate to their maximum speed of 5000 rpm for 2.5 seconds and then return to their set speed.


Release and pull the left trigger (30) rapidly to activate the Boost function.



Note

The Boost function can be activated at any time in both automatic or manual mode. It is useful when mowing irregularities are encountered (tall, dense grasses, etc.) and avoids having to change the initial settings of the mower.

5.3.5. COMBINATION OF CONTROLS



59N_19_022


Movement	Control
Advance + Turn left	A+C
Advance + Turn right	A+D
Reverse + Turn left	B+C
Reverse + Turn right	B+D
Turn the cutting blades + Advance	(E+F)+A
Turn the cutting blades + Reverse	(E+F)+B
Turn the cutting blades + Turn left	(E+F)+C
Turn the cutting blades + Turn right	(E+F)+D
Turn the cutting blades + Advance + Turn left	(E+F)+A+C
Turn the cutting blades + Advance + Turn right	(E+F)+A+D
Turn the cutting blades + Reverse + Turn left	(E+F)+B+C
Turn the cutting blades + Reverse + Turn right	(E+F)+B+D

5.3.6. LOCK / UNLOCK THE FRONT WHEELS DIRECTION

To lock the rotation of the front wheels, turn the 2 pins in front of each wheel to the horizontal.


In this position, the front wheels stay straight and the mower moves only in a straight line. A deliberate change of direction to the right or to the left nevertheless releases the wheels, which are then free to turn.

When the front wheels are back in a straight aligned position, they lock again in the straight ahead direction.



To lock the rotation of the front wheels, turn the 2 pins in front of each wheel to the vertical.

In this position, the front wheels are free and the mower can be turned in any direction without constraints.



5.3.7. ENABLE/DISABLE THE PARKING BRAKE/TRANSPORT BRAKE


To make the lawn mower secure on sloping or tilted ground, remember to apply the parking brake when at a stop and the cutting blades are not turning. When the parking break is enabled, the cutter deck housing comes into contact with the rear wheels and acts as a brake. The mower can therefore neither move forwards nor reverse and cannot be pushed.

Activating the parking brake

- Regardless of the cutting height set, press and hold on the '-' (22) button. The cutter deck housing lowers until it blocks the wheels. The letter 'P' flashes on the display

Deactivating the parking brake

- Press and hold the '+' (24) button, the cutting deck returns to the set cutting height. The display then indicates the cutting height.



Note

if the set cutting height is h25, a short single press on "-" (22) or "+" (24) can be used to respectively activate or deactivate the parking/transport brake.

Note

When the brake is activated, the blades and the wheels are deactivated.


**Caution**

Always check the blades and wheels have stopped before putting on the brake.

5.4. IMMOBILIZER SYSTEM**5.4.1. SECURITY KEY****Note**

This lawn mower is fitted with a key immobilizer system that prevents the motor from starting if the key is not in its socket. This system helps to limit the risks of accidents and theft.

Insert the security key (19) into the socket (18).



59N_18_053

**Caution**

Always remove the key from its socket when the work is finished. Keep the key with you or in a secure place where it cannot be accessed by unauthorized persons.

If the key is pulled out or not detected, the lawn mower will stop immediately. To restart the mower, turn off the battery, insert the security key in its socket and turn the battery back on. The mower will once again be ready to operate.

5.4.2. INCLINOMETER


Note

This lawn mower is equipped with an inclinometer that prevents engine start up when the mower is steeply inclined or turned over.

For your safety, it is impossible to start the blades when the mower is in a vertical position:

- for cleaning
- for unclogging
- to change worn parts

If the battery is operating, an intermittent beep shows that the mower is in a dangerous position with the battery enabled.



Caution




If the ground to be mowed is steep, there may be too much of a tilt on the mower and the motor will not start because of this safety feature.

If the mower is not located on level ground (slope <math><20^\circ</math>), an error code "SEC" corresponding to the safety shut down of the mower will appear on the control box.

If the blades are already moving, turning the mower into a vertical position or tipping it over will not stop the blades

Flashing error code for safety shut down:




5.5. ADVICE FOR USE

To get the best results when mowing a lawn and save time you should follow a certain method. Mow from the edge to the center. You should mow transversely. To make the height of the grass even, you should cut in different

directions. However, you should take greater care when mowing on sloping ground to avoid tipping the lawn mower. After mowing, the cut grass must be collected if it has not been mulched. Otherwise, residue can choke the lawn and prevent it from keeping its green color.

5.5.1. MOWING METHOD

1. Clear the edges of the area, if possible using the mower, otherwise using a brush cutter.
2. Mow by going forwards and backwards, first length-wise.
3. Then change direction and mow crosswise.
4. Try to overlap slightly on the previous line to attenuate the mowing lines and obtain a uniform lawn.



59N_18_058


Note

Try to overlap slightly on the previous line to attenuate the mowing lines and obtain a uniform lawn.

5.5.2. CUTTING HEIGHT

The cutting height depends both on the type of lawn that has been sown and the aesthetic appearance you wish to obtain:

- For a recreational lawn [A], (family garden), mow to a height of 35 to 75 mm.
- For an ornamental lawn [B], (municipal and town gardens) mow to a height of 35 mm.
- For a sports ground [C], (stadiums, golf courses, play areas) mow to a height of 45 to 65 mm.
- For a meadow [D], mow to a height of 75 mm.



59N_19_024


Note

- Ensure that you do not cut more than 1/3 of the height of the grass each time that you mow.
- Close cutting implies more frequent mowing.
- High cutting allows the grass to root deeper.

5.5.3. SLOPES

Although they are increasingly safe, lawn mowers are still dangerous machines, this is why it is better to mow across sloping ground rather than up and down to avoid any risk of tipping.

Take extra care if the lawn is slippery, you may lose control of the lawn mower and injure yourself.




59N_19_025

5.5.4. DAMP GROUND

Mowing when the grass is wet can force and stall the mower by jamming in the cutter deck housing. Before starting work in the morning, it is better to wait until the area to be mowed is completely dry to avoid damaging the mower.

Mow preferably in dry weather. The quality of the work done will only be more efficient, faster, more energy efficient and less difficult for the mower.




59N_18_061

5.5.5. MOWING WITH GRASS COLLECTION

Using the collecting bin allows you to have a clean lawn more quickly, without having to go over it a second time with a rake to collect the cut grass.

The collecting bin is easy to fit and remove, without tools, using its handles (15).



59N_19_027

Note

Mowing with collection allows you to obtain a neat and clean lawn. The risk of lawn diseases is reduced as the waste does not decompose directly on the ground.

5.5.6. MOWING WITHOUT GRASS COLLECTION

This type of mowing is suited for meadows or high and uneven grass.

No collecting bin is required for this type of mowing.

**Note**

You just need to remove the collecting bin in order for the cut grass to be ejected from the rear of the lawn mower.

5.5.7. MOWING WASTE**- 5.5.7.1. LEFT IN PLACE**

For a recreational lawn, you can leave the cuttings in place if you mow regularly as the cutting height will be lower and the grass finely cut.

Note

The cut part must however not exceed 2-3 cm!

- 5.5.7.2. COMPOSTING

The cut grass can be composted, alone or mixed with other garden and kitchen waste. However, take care not to put more than 5 cm of fresh cuttings in the composter as this material is high in nitrogen, which can release heat and bad smells.

Note

If volumes to compost are too high, leave the cuttings to dry in the sun for a day by spreading them on the ground to accelerate the decomposition process and prevent bad odors from being released.

- 5.5.7.3. USE CUTTINGS AS MULCH

Grass cuttings can also be used as mulch. For this, spread them at a thickness of 2 to 3 cm around your vegetable patches (tomatoes, aubergines, beans, etc.), on bare ground around your plants, or at the foot of trees and shrubs.

Note

This mulching limits evaporation during dry periods and will save on watering.

- 5.5.7.4. TURN CUTTINGS INTO ASH

You can also burn the waste to recover ashes that are rich in potassium. They can then be used around plants or spread on your lawn.

Note

French regulations regarding burning green waste

A circular was sent to Prefects in France on 18 November 2011 recalling the legal basis for the prohibition of burning green waste in the open air. It covers both private individuals and professionals working in green spaces who must eliminate their waste through mulching on-site, by taking it to a waste center or by direct recycling.

Only the Prefect may authorise a derogation to this rule when suggested by the health authority and after consultation with the regional health and technological and environmental authority (CODERST).

6. MAINTENANCE

6.1. MAINTENANCE FREQUENCY

Elements concerned	Operations	Frequency				Difficulty	Notes
		Prior to each use	After each use	Every 50 hours	When necessary		
General appearance	Visual inspection	X	X			1	
	Cleaning			X		1	
Handles / Triggers	Operation	X				1	
Screws and fittings (other than blades)	Tightening			X		1	
Cutter deck housing	Cleaning		X			1	Check that no debris is clogging the cutter deck housing that could block the blades from turning.

Elements concerned	Operations	Frequency				Difficulty	Notes
		Prior to each use	After each use	Every 50 hours	When necessary		
	Fastenings for the blades	X				1	Check the tightening of the nut that holds each blade
	Sharpening				X	2	Check that the blades are not blunt or damaged.
	Adjustment	X				1	Check that the blades are perpendicular
Battery	Please refer to the battery operating instructions						

6.2. USEFUL ADVICE FOR RISK FREE MAINTENANCE

Maintenance on the different parts of the lawn mower is important, it will ensure its service life longevity.



Caution


Always disconnect the lawn mower from the battery before working on the cutting blades.
Always turn off and remove the battery before cleaning the lawn mower with a water jet.
Always use products that are certified as compliant with your lawn mower.
In the event of any problem, consult an authorized distributor.

6.2.1. CUTTING BLADES

The cutting blades ensure the grass is cut cleanly. A high quality mower blade cuts the grass cleanly without ripping or shredding. Any bent, worn or perforated blades must be changed.

These parts must be replaced as a precautionary measure or at least once a year:

1. Rasion collection blade maintenance kit (see Section 9, "ACCESSORIES AND CONSUMABLES").
- OR
2. Rasion universal blade maintenance kit (see Section 9, "ACCESSORIES AND CONSUMABLES").



Important

For your safety, the blades and retaining pins must be checked immediately after an impact.


Tip the lawn mower upright. If the cutting blades are not perpendicular to each other, it may be because the retaining pins are broken.

In this case the mower must not be used to cut grass and the retaining pins must be replaced before the next use.


Before changing the retaining pins, check the state of wear of the cutting blades that can be replaced at the same time.

In case of excessive vibration, replace the blades:

- Unscrew and remove in order the 19mm nut, the Belleville washer and the cutting blade.
- Replace old pins with new pins if necessary.
- Sharpen the blade with a smooth-cut file following the bezel, filing only in one direction, from the inside to the outside of the blade, in one or two movements.
- Check that the blade is well balanced.
- Refit the blade in the direction of assembly, with tightening torque of 35 Nm.



59N_18_072



59N_18_073




Caution

Always disconnect the lawn mower from the battery before working on the cutting blades.

6.2.2. CUTTER HOUSING

Clean the inside and the outside of the housing after each mowing session:

- Tip the lawn mower upright.
- Use a wooden or plastic tool to scrape grass from inside the housing, taking care not to scratch the housing.
- Clean the rest of the mowing residue using a low pressure water jet.



59N_18_066



Caution

Always wear gloves to protect your hands and wrists when working near the cutting blades on the lawn mower! Danger of accidental cuts.



Warning


Never use soap or solvents, (such as trichloroethylene, white spirit or petrol, etc.) to clean the mower.

6.2.3. WHEELS

The lawn mower's wheels are particularly susceptible to clogging. Grass stalks, dust and mowing residues stick to the outer tires of the wheels and reduce the adhesion of the machine.

Clean the wheels after each mowing session.

Use a water jet to remove accumulated matter from the wheels.




59N_18_067

6.2.4. COLLECTING BIN

The collecting bin should always be cleaned thoroughly with a water jet after use and left to dry upside down in the sun to kill any mushroom spores and fungal diseases.

Empty the collecting bin regularly when mowing to ensure that the breathable fabric is clean.

The collecting bin is properly filled by the air flow created by the blades, which sends the cuttings into the collecting bin and are then evacuated by vents.



59N_18_068

6.2.5. CLEANING THE OPTICAL SENSOR

Turn off the battery.



Warning

Always clean the optical sensor with water and a wet cloth then turn the battery back on.

Never use solvents!

7. INCIDENTS AND TROUBLESHOOTING

Problem	Check	Probable cause	Possible action
The lawn mower does not start	display	Battery is off	Switch on the battery
		Battery discharged	Charge the battery
		Wrong connection with the battery	Check the power cord Check the connections (tool and battery). Clean them with compressed air if necessary Repeat the operation if necessary
	display	Faulty control	<ul style="list-style-type: none"> • Turn the battery off • Unplug the power cord and reconnect it • Restart the battery
		Safety at start up	Check that the security key is correctly inserted
SEC display	Cutter deck housing clogged	<ul style="list-style-type: none"> • Turn the battery off • Clean the inside of the housing • Restart the battery 	
	Internal fault	Contact your approved distributor	
The lawn mower tries and fails to start	Mower safety shut down (immobilizer)	Move the mower to a slope or tilt of less than 20°	
	Cutter deck housing clogged	<ul style="list-style-type: none"> • Turn the battery off • Clean the inside of the housing • Restart the battery 	
The lawn mower stops and starts	Display	The On/Off switches are defective	Contact your approved distributor
	Display	Cutter deck housing clogged	<ul style="list-style-type: none"> • Turn the battery off • Clean the inside of the housing • Restart the battery
		Damaged power cords	Contact your approved distributor

Problem	Check	Probable cause	Possible action
The lawn mower is not cutting grass properly		Grass is too high	Increase the cutting height
		Cutter deck housing clogged	<ul style="list-style-type: none"> • Turn the battery off • Clean the inside of the housing • Restart the battery
		Collecting bin full	Empty the collecting bin
		Turning speed of the blades is too slow	Increase the turning speed of the blades
		Damaged or blunt blades	Sharpen or replace the blades
		Blades mounted upside down	Refit the blades in the correct direction
		Retaining pins broken	Replace broken pins with new pins
Turning speed of the blades is too slow	Rotational speed < 2,500 rpm	Current settings are not suitable for mowing	<ul style="list-style-type: none"> • Increase the cutting height • Reduce the forward speed of the mower
The lawn mower stops	“HOT” display	The lawn mower has overheated	<ul style="list-style-type: none"> • Allow the lawn mower to cool down • Reduce the forward speed of the mower • Increase the cutting height of the mower
	“OPT” display	Density sensor clogged	<ul style="list-style-type: none"> • Switch to manual mode or • Switch off the battery/Clean the density sensor with water and a wet cloth/ Turn the battery back on
	The display is not powered	The battery is flat	Recharge the battery using the battery charger
The battery beeps then goes off	1 long beep + 1 short beep	Power surge alarm	Grass too high or too dense
	1 long beep + 2 short beeps	Lawn mower temperature alarm	Allow the lawn mower to cool down
	1 long beep + 3 short beeps	Over voltage or under voltage alarm	Battery flat or damaged
	1 long beep + 4 short beeps	Blockage safety alarm	Turn off the battery/Unblock the blades and/or clean the housing/Restart the battery
	1 long beep + 5 short beeps	Motor alarm	Contact your approved distributor
	1 long beep + 6 short beeps	Trigger alarm	Handlebar cable damaged

Problem	Check	Probable cause	Possible action
			Contact your approved distributor
		Key alarm	Security key missing, put the key back in the slot

8. STORAGE AND TRANSPORT

8.1. FOLD THE MOWER INTO THE TRANSPORT POSITION

1. Remove and safely store the security key.
2. Check that the battery is off, battery power icon off (750/1200/1500 battery).
3. Disconnect the battery from the mower.

To reduce the bulk of the mower in transport, fold back the handlebar (1).


4. Unlock the handlebar adjustment lever (5) by pulling it forwards.




5. Tilt the handlebar (4) forwards.



6. Lock the handlebar adjustment lever (5) by pulling it forwards.



7. Lock the transport brake.




Warning

Always make sure the battery is turned off before folding back the handlebar (4).

8.2. STORAGE

- Store the lawn mower in a dry, sheltered place.
- Remove and safely store the security key.
- Check that the battery is off, battery power icon off (750/1200/1500 battery).
- Disconnect the battery from the mower.
- To reduce the size of the mower in storage, fold down the handlebar (4) (see Section 8.1, “Fold the mower into the transport position”).




Warning

Always make sure the battery is turned off before folding the handlebar (4).

8.3. OFF-SEASON STORAGE

Before stowing the lawn mower for the winter, remember to have it serviced by an Approved Specialist.

- Check that the battery is off, battery power icon off (750/1200/1500 battery).
- Disconnect the battery from the mower.
- Remove the battery from its tray.
- To reduce the size of the mower during storage, fold the mower into the transport position (see Section 8.1, "Fold the mower into the transport position").
- Recharge the battery using its charger following the instructions in the user manual.
- Store the battery in a frost-free place.



59N_19_030

Note


Have your lawn mower serviced every 200 hours or at least once a year. Always make sure the mower is clean and the battery charged before storage.

9. ACCESSORIES AND CONSUMABLES


Name		reference
Maintenance kit	Rasion collecting blades	131404 (standard)
	Rasion universal blades	134104
Collecting bin		145870
Mulching kit		57154
Battery protection kit	750/1200/1500 Batteries	135454
Security key with ring		130424

Name	reference	
750/1200/1500 battery holder kit	135161	
1200 Ultra Lithium Battery	57253	
1500 Ultra Lithium Battery	57254	

59_20_167

Name	reference	
750/1200/1500 battery holder kit	135161	
750 Ultra Lithium Battery	57191	

59_20_250

Name	reference	
Battery holder included in the comfort harness	57194	
PELENC ALPHA 260 battery	57192	
PELENC ALPHA 520 battery	57193	

59_20_166

10. GENERAL WARRANTIES

10.1. STATUTORY WARRANTY

10.1.1. LATENT DEFECTS WARRANTY

Apart from the commercial warranty provided for under Article II, Article 1641 of the Civil Code provides that "the seller is bound to a warranty on account of latent defects of the object sold which render it unfit for the use for which it was intended, or which would impair said use to the extent that the buyer would not have acquired it, or would only have given a lesser price for it, had he known of them".

Article 1648 of the Civil Code "The action resulting from latent defects must be brought by the purchaser within two years after the discovery of the defect. "

10.1.2. LEGAL WARRANTY OF CONFORMITY

Article L.217-4 of the Consumer Code "The seller delivers goods in conformity with the contract and is liable for defects of conformity existing upon delivery.

The seller is also liable for any lack of compliance resulting from the packaging, assembly or installation instructions whenever its contractual liability is engaged in this regard or the latter are carried out under its responsibility

Article L.217-5 of the French Consumer Code "Goods are compliant with the contract":

1. Where they are fit for the purpose normally expected of similar goods and, where applicable:
 - If it matches the description given by the seller and possesses the qualities that were presented to the purchaser in the form of a sample or model;
 - If it possesses the qualities that a purchaser can reasonably expect given the public statements made by the seller, the producer or its representative, especially in advertising or labelling;
2. Or, if it has the characteristics defined by mutual agreement of the parties or is fit for any particular purpose that the buyer made known to the seller and that the latter accepted.

Article L.217-12 of the Consumer Code "legal action resulting from lack of conformity lapses two years after delivery of the goods".

10.2. COMMERCIAL WARRANTY PELLENC

10.2.1. CONTENT

- 10.2.1.1. GENERAL INFORMATION

In addition to legal warranties, client users benefit from the commercial warranty on products PELLENC covering the exchange and replacement of parts recognised as being out of order, due to machining defects, assembly defects or material defects, whatever the cause.

The warranty is fully integral to the product sold by PELLENC.

- 10.2.1.2. SPARE PARTS

The commercial warranty also covers original PELLENC spare parts, excluding labour and to the exclusion of certain parts of each product provided at delivery.

10.2.2. DURATION OF THE WARRANTY

- 10.2.2.1. GENERAL INFORMATION

PELLENC Products are guaranteed under the commercial warranty as from delivery to the customer for a period of two (2) years for products connected to a PELLENC battery, and for a period of one (1) year for other PELLENC products.

- 10.2.2.2. SPARE PARTS

PELLENC Replacement parts replaced under the product warranty are guaranteed under the commercial warranty as from delivery of the PELLENC product to the customer user for a period of two (2) years for products connected to a PELLENC battery, and for a period of one (1) year for other PELLENC products.

In the case of products connected to a PELLENC battery, parts that are replaced under the product warranty after the 12th month of use, are covered for a period of one (1) year.

- 10.2.2.3. WARRANTY EXCLUSIONS

Excluded from the commercial warranty are products that have been subject to abnormal use, or were used under conditions and for purposes other than those for which they were manufactured, especially in the case of non-compliance with conditions stipulated in this user manual.

It does not apply in case of shock, fall, neglect, lack of supervision or maintenance or in case of transformation of the product. Also excluded from the warranty are products that have been subject to tampering, alteration or modification by the client user.

Wear parts and/or consumables cannot be covered by the warranty.

10.2.3. IMPLEMENTATION OF THE COMMERCIAL WARRANTY

- 10.2.3.1. PRODUCT COMMISSIONING AND COMMISSIONING DECLARATION

The DISTRIBUTOR undertakes to complete the computer commissioning declaration form, no later than eight days after the delivery of the property to the user customer, in order to activate the latter on the www.pellenc.com website under "warranties and training" in the "extranet" menu, using the identifier previously provided to them by PELLENC.

Failing that, commissioning declaration will not be effective and implementation of the commercial warranty PELLENC will not occur. As a consequence thereof, the DISTRIBUTOR must ensure the financial burden of its intervention under the warranty without being able to pass on the cost to the client user.

The DISTRIBUTOR shall also undertake to complete the warranty card or the certificate of warranty and commissioning for self-propelled equipment provided with the product after having the client user sign and date it.

10.3. PAID AFTER-SALES SERVICE

10.3.1. GENERAL INFORMATION

Malfunctions, breakdowns, breakages resulting from misuse, neglect or improper maintenance by the client user as well as malfunctions resulting from normal wear of the product are subject to the payment of after-sales service, even during the period of the legal and commercial warranty. After-sales service repairs that fall outside of the legal and commercial warranty also include maintenance, adjustments, diagnostics of all types, and cleaning without the present list being exhaustive.

10.3.2. WEAR PARTS AND CONSUMABLES

Wear parts and consumables also fall within the after-sales service.

10.3.3. SPARE PARTS

Paid after-sales service also covers original PELLENC spare parts, excluding labour and outside the legal and commercial warranty period.

In case of replacement of original PELLENC spare parts in the context of after-sales service, said latter are covered by a warranty of one year as from the installation date.

11. COMPLIANCE STATEMENTS

11.1. "EC" DECLARATION OF CONFORMITY: RASION 2

MANUFACTURER	PELLENC
ADDRESS	Quartier Notre-Dame - 84120 Pertuis (France)

ENTITY AUTHORIZED TO COMPILE THE TECHNICAL FILE	PELLENC
ADDRESS	Quartier Notre-Dame - 84120 Pertuis (France)

We hereby declare that the machine referred to below as:

GENERIC DENOMINATION	Lawn mower	
FUNCTION	Battery-powered self-propelled mower intended for the maintenance of green spaces	
COMMERCIAL NAME	RASION 2	
TYPE	RASION 2	
MODEL	EASY	SMART
SERIAL No.	59U00001 - 59U49999 59V00001 - 59V49999 59W00001 - 59W49999	

Complies with the relevant provisions of the machinery directive (2006/42/EC).

Complies with the provisions of the following European directives:

- 2014/30/EU EMC Directive
- 2011/65/EU ROHS Directive
- 1907/2006 REACH Regulation
- 2012/19/EU WEEE Directive
- 2000/14 / EC Directive on environmental noise emissions

The following harmonised European standards have been used in whole or in part:

- EN 60335-1: 2012
- EN 60335-2-77: 2010
- EN 55014-1: 2006 + A1: 2009 + A2: 2011
- EN 55014-2: 1997 + A1: 2001 + A2: 2008

Sound level at maximum speed:

Symbol	Value	Unit	Reference	Remark
LWAm		dB(A)		Measured sound power level
LWAg		dB(A)		Guaranteed sound power level

The measured sound level and the guaranteed sound power level were measured according to a procedure in accordance with Directive 2000/14 / EC Annex V.

SIGNED IN PERTUIS, DATED 27/08/2020
JEAN-MARC GIALIS
CEO



PELLENC

   www.pellenc.com

PELLENC
Quartier Notre Dame - 84120 Pertuis (France)

